

1. PRODUCT NAME

Sport-Top™

2. MANUFACTURER

Neyra Industries, Inc.
10700 Evendale Drive
Cincinnati, Ohio 45241

Phone: 513-733-1000
Toll Free: 800-543-7077
Fax: 513-733-3989
Email: info@neyra.com
Website: www.neyra.com

- **Premium Acrylic Cushion Coating System:** A durable coating for tennis courts and running tracks.
- **Specially Formulated:** 100% compatible with Dynaflex Acrylic Color Coating.
- **Fast Drying:** Acrylic formula allows for faster drying than asphalt-based coatings.
- **Multi-Layer:** Designed as a cushion coat prior to application of Dynaflex Acrylic Color Coating finish.
- **No Harmful Solvents:** Can be used indoors as well as outdoors.

3. PRODUCT DESCRIPTION

Sport-Top is a rubberized synthetic polymer emulsion coating containing mineral fillers and fine rubber particles.

Packaging:

Packaged in 55 gal. steel drums.

Color:

Sport-Top is made to order and available in black.

Basic Uses:

Sport-Top is designed as a levelling cushion inter-layer when installing the Dynaflex Cushion System to tennis courts and similar recreational surfaces. Sport-Mat should be applied prior to Sport-Top and Dynaflex Color Coating should be applied after Sport-Top. The Sport-Top will level and fill textured surfaces resulting from Sport-Mat's larger rubber granules.

Although Sport-Top is intended to be coated with Dynaflex Color Coating, it can be used as a finish coat if desired.

Composition:

As shipped, Sport-Top is a synthetic polymer emulsion.

Limitations:

In the liquid state, Sport-Top must be protected from freezing and rain. Do not store in direct sunlight or where temperature exceeds 120°F.

4. INSTALLATION

Preparatory Work:

The surface must be structurally sound, surface cured and free from all loose or foreign matter prior to the application of Sport-Top.

Methods:

Because Sport-Top is designed to increase cushion, build up and level cushion surface prior to Dynaflex Color Coating. Sport-Top should be applied by squeegee. Mix thoroughly before use.

Mix Design:

As supplied, Sport-Top is a concentrated material intended to be mixed with up to 20 gal. of water/55 gal. of Sport-Top concentrate to achieve a heavy, creamy consistency for application.

Application:

The following application procedures are recommended for best results:

Each application shall be at a rate of 7-10 sq. yd./gal. concentrate/coat (0.1 to 0.14 gal./sq. yd.). Coverage rates can vary with the age, texture, and porosity of the pavement to be sealed.

Application must be made when ambient and pavement temperatures are above 50°F.

It is recommended that the area over which the application is made be open to use only after trial shows it to be cured sufficiently.

Precautions:

Wet Sport-Top must be protected at all times from freezing. Keep out of reach of children. Container should be closed when not in use. Avoid breathing vapor or contact with skin or eyes. Consult specific Neyra material safety data sheet before use.

New asphalt should be allowed to cure for a minimum of 15 days prior to application and must not exhibit ribboning, crawling, nor show oil rings when 1 gal. of clean water is poured onto the surface.

5. MAINTENANCE

Proper care of the finished surface will maintain the attractive appearance and prolong the service of the Dynaflex coating system. Keeping leaves and other foreign matter off the surface and occasional flushing with clean cold water will achieve good results.

6. TECHNICAL DATA

Adhesion and Resistance to Water:

The cured coating exhibits no penetration, blistering, loss of adhesion, nor tendency to re-emulsify after immersion for 24 hours. Complete sampling and test procedures are available upon request.

Environmental Considerations:

Sport-Top is considered non-hazardous when tested according to the EPA's TCLP (Toxicity Characteristic Leaching Procedure). Sport-Top is a water-based material containing less than 70 g/L (0.58 lbs./gal.) VOC content.

7. TECHNICAL SERVICES

C.S.I. formatted application specifications, material safety data sheets, special project submittals, product and application recommendations as well as assistance with special situations and field service are available.

8. WARRANTY

The above specifications on product usage are believed to be true and accurate. Neyra Industries, Inc. guarantees that all materials manufactured comply with quality standards as described in the product data sheets. Because the application, handling, weather, workmanship and equipment are beyond the control of this manufacturer, only the quality of the products as shipped is guaranteed. In no case will the liability of Neyra Industries, Inc. exceed the purchase price of the shipped materials.

9. ADDITIONAL INFORMATION

Neyra Industries, Inc. manufactures a full line of recreational surface and asphalt pavement maintenance products as well as application equipment sold and distributed nationally at our plants and through distributors and contractors. To find the supplier most convenient to you, please contact us.

NEYRA

**Neyra Industries, Inc.
10700 Evendale Drive
Cincinnati, Ohio 45241**

Phone: 513-733-1000

Toll Free: 800-543-7077

Fax: 513-733-3989

Email: info@neyra.com

Website: www.neyra.com