

Issuing Date 23-May-2011

Revision Date

Revision Number 0

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name Asphalt Tac Tack Coat
Product Code(s) 156
Recommended Use Refer to the Product Data Sheet for Additional Information.

Supplier Address

Neyra Industries, Inc.
10700 Evendale Drive
Cincinnati, Ohio 45241
TEL: (513) 733-1000

Company Emergency Phone Number (513) 733-1000**2. HAZARDS IDENTIFICATION****WARNING!****Emergency Overview**

Vapors may be irritating to eyes, nose, throat, and lungs
Contains a known or suspected carcinogen

Appearance Brown**Physical State** Liquid.**Odor** Asphaltic**Potential Health Effects****Principle Routes of Exposure** Inhalation. Skin contact. Eye contact.**Acute Toxicity****Eyes**

May cause irritation.

Skin

May cause irritation.

Inhalation

May cause irritation of respiratory tract.

Ingestion

Ingestion may cause irritation to mucous membranes.

Chronic Effects

The International Agency for Research on Cancer (IARC) has determined that there is inadequate evidence that undiluted, air-refined asphalt is carcinogenic to experimental animals. Limited evidence exists that undiluted steam-refined and cracking residue asphalts is carcinogenic to animals. Additionally, IARC has concluded that there is inadequate evidence that asphalts alone are carcinogenic to humans.

Aggravated Medical Conditions

Pre-existing eye disorders. Skin disorders. Respiratory disorders.

Environmental Hazard

See Section 12 for additional Ecological Information.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS-No	Weight %
Asphalt	8052-42-4	55-65

4. FIRST AID MEASURES

Eye Contact	Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.
Skin Contact	Wash off immediately with soap and plenty of water. Consult a physician.
Inhalation	Move to fresh air. If symptoms persist, call a physician.
Ingestion	Clean mouth with water and afterwards drink plenty of water. If symptoms persist, call a physician.
Notes to Physician	Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Flammable Properties	Not flammable.			
Flash Point	Not determined.			
Suitable Extinguishing Media	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.			
Hazardous Combustion Products	Hydrocarbons. Hydrogen sulfide.			
Explosion Data				
Sensitivity to Mechanical Impact	None			
Sensitivity to Static Discharge	None			
Specific Hazards Arising from the Chemical	Thermal decomposition can lead to release of irritating gases and vapors.			
Protective Equipment and Precautions for Firefighters	As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.			
NFPA	Health Hazard 2	Flammability 0	Instability 0	Physical and Chemical Hazards -
HMIS	Health Hazard 1*	Flammability 0	Physical Hazard 0	Personal Protection X

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions	Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak. Use personal protective equipment. Avoid contact with skin, eyes and clothing.
Environmental Precautions	Do not allow material to contaminate ground water system. Do not flush into surface water or sanitary sewer system.
Methods for Containment	Dike far ahead of liquid spill for later disposal.
Methods for Cleaning Up	Use personal protective equipment. Dam up. Soak up with inert absorbent material. Sweep up and shovel into suitable containers for disposal. Keep in suitable and closed containers for disposal.

7. HANDLING AND STORAGE

Handling	Wear personal protective equipment. Ensure adequate ventilation. Keep away from open flames, hot surfaces and sources of ignition. Avoid breathing vapors or mists. Avoid contact with skin, eyes and clothing. Remove and wash contaminated clothing before re-use.
Storage	Keep away from open flames, hot surfaces and sources of ignition. Keep container tightly closed in a dry and well-ventilated place. Do not freeze. Do not store in direct sunlight or in temperatures exceeding 120°F (48.9°C).

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Asphalt 8052-42-4	TWA: 0.5 mg/m ³ benzene soluble aerosol fume, inhalable fraction		Ceiling: 5 mg/m ³ fume 15 min

OSHA PEL: Occupational Safety and Health Administration - Permissible Exposure Limits. ACGIH TLV: American Conference of Governmental Industrial Hygienists - Threshold Limit Value. NIOSH IDLH: Immediately Dangerous to Life or Health.

Other Exposure Guidelines Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992).

Engineering Measures Showers
Eyewash stations
Ventilation systems

Personal Protective Equipment

Eye/Face Protection
Skin and Body Protection
Respiratory Protection

Safety glasses with side-shields. If splashes are likely to occur, wear: Goggles.

Wear protective gloves/clothing.

If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.

Hygiene Measures When using, do not eat, drink or smoke. Remove and wash contaminated clothing before re-use. Provide regular cleaning of equipment, work area and clothing.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	Brown.	Odor	Asphaltic.
Odor Threshold	No information available.	Physical State	Liquid.
pH	6.0 - 8.0	Autoignition Temperature	No information available.
Flash Point	No information available.	Boiling Point/Boiling Range	100°C / 212°F
Decomposition Temperature	No information available.	Explosion Limits	No information available.
Melting Point/Range	No information available.	Water Solubility	Partly soluble.
Flammability Limits in Air	No information available.	Evaporation Rate	No information available.
Specific Gravity	1.02	Vapor Density	No data available.
Solubility	No information available.		
Vapor Pressure	No data available.		
EPA VOC (g/l)	0		

10. STABILITY AND REACTIVITY

Stability Stable under recommended storage conditions.

Incompatible Products Strong oxidizing agents. Do not apply over chip seals or sealers containing gilsonite. Not recommended for use on portland cement, concrete or for indoor use.

Conditions to Avoid Keep away from open flames, hot surfaces and sources of ignition.

Hazardous Decomposition Products Carbon monoxide (CO). Carbon dioxide (CO₂). Hydrocarbons. Hydrogen sulfide. Sulfur oxides.

Hazardous Polymerization Hazardous polymerization does not occur.

11. TOXICOLOGICAL INFORMATION

Acute Toxicity

Product Information No acute toxicity information is available for this product.

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
Asphalt	5000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	

Chronic Toxicity

Chronic Toxicity

The International Agency for Research on Cancer (IARC) has determined that there is inadequate evidence that undiluted, air-refined asphalt is carcinogenic to experimental animals. Limited evidence exists that undiluted steam-refined and cracking residue asphalts is carcinogenic to animals. Additionally, IARC has concluded that there is inadequate evidence that asphalts alone are carcinogenic to humans.

Carcinogenicity

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
Asphalt		Group 2B Group 3		X

IARC: (International Agency for Research on Cancer)

Group 2B - Possibly Carcinogenic to Humans

Group 3: Not Classifiable as to its Carcinogenicity to Humans

OSHA: (Occupational Safety & Health Administration)

X - Present

Target Organ Effects

Respiratory system.

12. ECOLOGICAL INFORMATION

Ecotoxicity

The environmental impact of this product has not been fully investigated.

Chemical Name	Log Pow
Asphalt	6.006

13. DISPOSAL CONSIDERATIONS

Waste Disposal Methods

This material, as supplied, is not a hazardous waste according to Federal regulations (40 CFR 261). This material could become a hazardous waste if it is mixed with or otherwise comes in contact with a hazardous waste, if chemical additions are made to this material, or if the material is processed or otherwise altered. Consult 40 CFR 261 to determine whether the altered material is a hazardous waste. Consult the appropriate state, regional, or local regulations for additional requirements.

Contaminated Packaging

Do not re-use empty containers.

14. TRANSPORT INFORMATION

<u>DOT</u>	Not regulated
<u>TDG</u>	Not regulated
<u>MEX</u>	Not regulated

15. REGULATORY INFORMATION

International Inventories

TSCA	Complies
DSL	Complies

Legend

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

U.S. Federal Regulations

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

Chemical Name	CAS-No	Weight %	SARA 313 - Threshold Values %
Asphalt	8052-42-4	60.5	0.1

SARA 311/312 Hazard Categories

Acute Health Hazard	No
Chronic Health Hazard	Yes
Fire Hazard	No
Sudden Release of Pressure Hazard	No
Reactive Hazard	No

Clean Water Act

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42).

CERCLA

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material.

U.S. State Regulations

California Proposition 65

This product does not contain any Proposition 65 chemicals.

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania	Illinois	Rhode Island
Asphalt	X	X	X		X

International Regulations

Chemical Name	Carcinogen Status	Exposure Limits
Asphalt		Mexico: TWA 5 mg/m ³ Mexico: STEL 10 mg/m ³

Canada

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR.

WHMIS Hazard Class

Non-controlled

16. OTHER INFORMATION

Prepared By Product Stewardship
23 British American Blvd.
Latham, NY 12110
1-800-572-6501

Issuing Date 23-May-2011

Revision Date

Revision Note Initial Release.

General Disclaimer

The information provided on this MSDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

End of Safety Data Sheet